

**Listing of Claims:**

Claims 1-28 (Canceled).

29. (Currently Amended) An image display device that:  
(i) projects, via a relay optical system, ~~each of the~~ lights  
emitted from each of two two-dimensionally light emitting type  
photoelectric devices which are perpendicular to ~~the~~ a light beam  
emitting direction onto first and second light diffusing bodies  
~~which that~~ are independent of each other relative to ~~the~~ right  
and left eyes of a user, and (ii) projects and images ~~the~~  
transmitted images of said light diffusing bodies onto a retina  
in the respective right and left eyes of the user [[,]] via first  
and second eyepiece optical systems which respectively correspond  
to the first and second light diffusing bodies, ~~onto the retina~~  
~~in the eyeball, with~~ wherein the imaged transmitted images ~~being~~  
~~a~~ are wide range image images having a field of view angle of at  
least  $\pm 22.5$  degrees, ~~or more, said image display device being~~  
characterized in that wherein said two two-dimensionally light  
emitting type photoelectric devices are each a reflection type  
liquid crystal device element, ~~in that~~ and wherein the image  
display device further comprises:

one light source,

20 a first polarization beam splitter that divides ~~the~~ light  
emitted from said light source into P-polarized light and  
S-polarized light, and

an optical system that leads each of the divided P-polarized  
light and S-polarized light respectively to said two  
25 two-dimensionally light emitting type photoelectric devices, ~~thus~~  
~~illuminates thereby illuminating~~ said two two-dimensionally light  
emitting type photoelectric devices, and

wherein the optical system leads the lights reflected  
thereby by each of said two two-dimensionally light emitting type  
30 photoelectric devices to said relay optical system ~~are provided,~~  
~~and in that said optical system leads the reflected lights to~~  
~~said relay optical system~~ via a second polarization beam  
splitter, and wherein the reflected lights being are one of the  
P-polarized ~~lights~~ light converted from the S-polarized ~~lights,~~  
35 light or being and the S-polarized ~~lights~~ light converted from  
the P-polarized ~~lights~~ light.

30. (Currently Amended) An image display device that:  
(i) projects, via a relay optical system, ~~each of the~~ lights  
emitted from each of two sets of two-dimensionally light emitting  
type photoelectric devices which are perpendicular to ~~the a~~ light  
5 beam emitting direction onto first and second light diffusing  
bodies ~~which that~~ are independent of each other relative to ~~the~~

right and left eyes of a user, and (ii) projects and images the transmitted images of said light diffusing bodies onto a retina in the respective right and left eyes of the user [[,]] via first and second eyepiece optical systems which respectively correspond to the first and second light diffusing bodies, ~~onto the retina in the eyeball, with wherein~~ the imaged transmitted images ~~being~~ are wide range ~~image~~ images having a field of view angle of at least  $\pm 22.5$  degrees, ~~or more, said image display device being~~ characterized in that and wherein each of said two sets of two-dimensionally light emitting type photoelectric devices ~~are each constituted by~~ comprises three reflection type liquid crystal device elements, each corresponding to ~~each one~~ of the colors of G, B, and R, ~~in that~~ and wherein the image display device further comprises:

      one light source,

      a first polarization beam splitter that divides ~~the~~ light emitted from said light source into P-polarized light and S-polarized light, and

      an optical system that leads each of the divided P-polarized light and S-polarized light respectively to said two sets of two-dimensionally light emitting type photoelectric devices, ~~thus illuminates thereby illuminating~~ said two sets of two-dimensionally light emitting type photoelectric devices, ~~and~~

30        wherein the optical system leads the lights reflected  
thereby ~~by said two sets of two-dimensionally light emitting type~~  
photoelectric devices to said relay optical system ~~are provided,~~  
and ~~in that~~

wherein said optical system respectively leads said  
35    P-polarized light ~~or~~ and S-polarized light to each of said two  
sets of two-dimensionally light emitting type photoelectric  
devices, which accommodate the colors of G, B, and R, via a  
second polarization beam splitter ~~,-a~~ and an RGB light beam  
division multiplexer prism, and leads the reflected lights to  
40    said relay optical system via said RGB light beam ~~dividing/~~  
multiplexing division multiplexer prism [[,]] and said second  
polarization beam splitter, and wherein the reflected lights  
~~being~~ are one of the P-polarized ~~lights~~ light converted from the  
S-polarized ~~lights,~~ light or being and the S-polarized ~~lights~~  
45    light converted from the P-polarized ~~lights~~ light.

31. (Currently Amended) ~~An~~ The image display device  
according to claim 29, wherein said light source ~~is~~ comprises a  
plurality of white light LEDs two-dimensionally arranged in an  
array form.

32. (Currently Amended) ~~An~~ The image display device  
according to claim 29, ~~characterized in that~~ wherein said light  
source ~~has~~ comprises:

5           a group of R color LEDs,  
          a group of G color LEDs, and  
          a group of B color LEDs, and  
          an RGB light beam division multiplexer prism that combines  
          lights emitted by the R, G and B groups,  
          wherein each group comprises ~~being constituted by a~~  
10   plurality of ~~the respective color~~ LEDs of the respective color  
          two-dimensionally arranged in an array form, ~~, and an RGB light~~  
          ~~beam division multiplexer prism that combines the lights emitted~~  
          ~~by those groups.~~

33. (Currently Amended) ~~An~~ The image display device  
according to claim 29, ~~characterized in that~~ wherein the optical  
system, which leads the light emitted from said light source to  
          each of said two two-dimensionally light emitting type  
5   photoelectric devices, ~~has~~ comprises an illumination uniformizing  
optical system.

34. (Currently Amended) ~~An~~ The image display device  
according to claim 33, ~~characterized in that~~ wherein said  
illumination uniformizing optical system ~~is~~ comprises at least  
one rod, ~~and in that the~~ wherein a final exit plane of said rod  
5   and ~~the~~ a surface of ~~said a corresponding~~ two-dimensionally light

emitting type photoelectric ~~devices~~ device are made substantially conjugate with each other.

35. (Currently Amended) ~~An~~ The image display device according to claim 30, wherein said light source ~~is~~ comprises a plurality of white light LEDs two-dimensionally arranged in an array form.

36. (Currently Amended) ~~An~~ The image display device according to claim 30, ~~characterized in that~~ wherein said light source ~~has~~ comprises:

a group of R color LEDs,

a group of G color LEDs, ~~and~~

a group of B color LEDs, and

an RGB light beam division multiplexer prism that combines lights emitted by the R, G and B groups,

wherein each group comprises being constituted by a  
plurality of ~~the respective color~~ LEDs of the respective color  
two-dimensionally arranged in an array form, ~~and an RGB light beam division multiplexer prism that combines the lights emitted by those groups.~~

37. (Currently Amended) ~~An~~ The image display device according to claim 30, ~~characterized in that~~ wherein the optical

system, which leads the light emitted from said light source to  
each of said two sets of two-dimensionally light emitting type  
5 photoelectric devices, ~~has~~ comprises an illumination uniformizing  
optical system.

38. (Currently Amended) ~~Am~~ The image display device  
according to claim 37, ~~characterized in that~~ wherein said  
illumination uniformizing optical system ~~is~~ comprises at least  
one rod, and ~~in that the~~ wherein a final exit plane of said rod  
5 and ~~the~~ a surface of ~~said~~ a corresponding set of  
two-dimensionally light emitting type photoelectric devices are  
made substantially conjugate with each other.

Claims 39-43 (Canceled).